



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

1250

1250



SPECIFICATIONS

Box Quantity	3-1/2" x 3-1/2", 2 per box. All other sizes, 3 per box.
Case Quantity	3-1/2" x 3-1/2" 80 per box. All others 48
Certifications	ANSI K81071F
Finishes	USP, US3, US4, US10, US10A, US10B, US26D
Gauge	See Sizing Chart Options
Height	See Sizing Chart Options
Knuckles	3
Material	Steel with Steel Components
Notes	<ul style="list-style-type: none"> • UL approved for use on doors 4'0" x 8'0", but Hager does not recommend using spring hinges on doors over 7'0" in favor of hydraulic door closers. • For maximum versatility use all spring hinges or a combination of spring hinges and ball bearing or anti-friction hinges. Do not use plain bearing hinges. Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges. Full spring tension may not be required on all hinges. • Doors over 3'0" x 7'0" or over 100 lbs require three spring hinges. Doors 150-180 lbs require four spring hinges.
Options	<ul style="list-style-type: none"> • Available with hospital tip (HT) - voids UL. • Available with raised barrel (RBB/RBS) - UL approved.
Product Description	Full Mortise, Spring Hinge, Standard Weight, Square Corner
Width	See Sizing Chart Options