



PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

276D

276D



SPECIFICATIONS

Bolt	1/4" x 3/4" (6 mm x 19 mm)
Bolt Throw	1" (25 mm)
Box Quantity	1
Case Quantity	12
Certifications	<ul style="list-style-type: none"><li>• UL listed for use on inactive leaf on a pair of 3-hour labeled fire doors</li><li>• Meets ANSI A156.16 for L04161 or L84161</li></ul>
Fasteners	<ul style="list-style-type: none"><li>• Eight #10-24x1" FPHMS</li><li>• Eight #10 x 1-1/4" undercut FPHWS</li></ul>
Finishes	US3, US10, US10B, US26D
Material	Steel
Notes	<ul style="list-style-type: none"><li>• Mortise bottom strike and universal top strike included</li><li>• Strong tension springs prevent creep</li><li>• Bar: 3/4" x 1/4" (19 mm x 6 mm) thick</li></ul>
Product Description	Surface Bolt: 12"
Projection	1-3/8" (35 mm)
Size	<ul style="list-style-type: none"><li>• Length: 12" (305 mm)</li><li>• Overall width: 2-1/2" (52 mm)</li></ul>