

282D

Manual Flush Bolt

Notes:

- Sold and priced in increments of 2
- 3-hour fire rating for metal doors up to 4 feet wide by 10 feet tall
- 282S strike plate bag and 282P bolt head available
- For use on hollow metal/fire rated doors
- 282R optional rod length available: 18" (457 mm) , 25" (635 mm), and 30" (762 mm) at no extra charge. Bolt head, if required, may be ordered separately as part number 282P.
- Non-handed
- Bolt head rods are adjustable



PRODUCT SPECIFICATIONS

CERTIFICATIONS:

- Meets ANSI 156.16 for L04251

FACE PLATE:

- 1" x 6-3/4" (25 mm x 172 mm)

FLATTENED ROUND BOLT HEAD:

- 1/2" (13 mm) square

BOLT THROW:

- 3/4" (19 mm)

STANDARD ROD LENGTH:

- 12" (305 mm) (from center of face to corner of door)

BOLT BACKSET:

- 3/4" (19 mm)

GUIDE PLATE:

- 1" x 2" (25 mm x 51 mm)

MORTISE STRIKE:

- 15/16" x 2-1/4" (24 mm x 57 mm)

OPTIONAL ROD LENGTH:

- 18" (457 mm)
- 25" (636 mm)
- 30" (762 mm)
- Specify 282R

MATERIALS:

- Brass faceplate with steel components

FINISHES:

- US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D

FASTENERS:

- Eight (8) #8 x 3/4" combo screws
- Eight (8) #8 x 1-1/2" combo screws