



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

292D

292D

Must be ordered in increments of two.



SPECIFICATIONS

Bolt	Backset: 3/4" (19.5 mm)
Bolt Throw	3/4" (19 mm)
Box Quantity	1 pr
Case Quantity	12 prs
Certifications	<ul style="list-style-type: none"> • 3-hour fire rating on metal doors up to 4' wide x 8' tall (A label rating) • Meets ANSI 156.3 Type #25
Faceplate	1" x 6-3/4" (25.6 mm x 171.8 mm)
Finishes	US10B, US32D
Flattened Round Bolt Head	1/2" (13 mm)
Includes	2 each 292
Material	Stainless steel with steel components
Mortise Strike Length	2-1/4" (57 mm)
Mortise Strike Width	15/16" (24 mm)
Notes	<ul style="list-style-type: none"> • Contains two 292S flush bolts • Thermal lock automatically locks inactive door under high fire/heat conditions • 280X dust proof strike are recommended for use with these sets • Used in pairs at top and bottom of inactive door • Fully automatic- bolts retract when active door is opened; bolts extend when active door is closed • Non-handed • Bolt head rods are adjustable • To only be used with non-beveled doors
Product Description	Automatic Flush Bolt Set for Metal Doors