

PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

3221 - THUMBTURN ONLY - E2192

3221











SPECIFICATIONS

Applications Standard Duty Commercial

Backsets Adjustable 2–3/8" - 2–3/4" (60mm - 70 mm)

Certifications • ADA Compliant ANSI A117.1 Accessibility Code

• UL/cUL Listed for all functions up to 3 hours "A" label single doors

UL10C Positive Pressure Rated

• BHMA Certified ANSI A156.36, Grade 2

• 1" (25 mm) Throw - Brass with concealed hardened steel roller to prevent sawing or

cutting

• 1-1/8" x 2-1/4" (29 mm x 57 mm) square corner faceplate

Door Thickness 1–3/8" – 1–3/4" (35 mm – 45 mm)

Exposed Trim Wrought Brass, Bronze or Stainless Steel

Finishes US3, US4, US10B, US26D and US32D

Functions Thumbturn Only (E2192)

Notes Non-handed

Options Additional Deadbolts and strikes available

Strikes • 3930 - 1-1/8" x 2-3/4" (29 mm x 70 mm) no-lip strike - standard

• 3929 - 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA deadbolt strike - optional

Warranty Lifetime