



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

3540 - PRIVACY - F76A

3540 LEVER



SPECIFICATIONS

Applications	Standard Duty Commercial
Backsets	<ul style="list-style-type: none"> 2-3/4" (70mm) 2-3/8" (60mm) 3-3/4" (94mm) 5" (128mm)
Certifications	<ul style="list-style-type: none"> ADA Compliant ANSI A117.1 Accessibility Code UL/cUL Listed for all functions up to 3 hours "A" label single doors UL10C Positive Pressure Rated BHMA Certified ANSI A156.2, Series 4000, Grade 2
Door Thickness	1-3/8" - 2" (35 mm - 51 mm)
Exposed Trim	Wrought brass, Bronze, and Stainless steel
Finishes	<ul style="list-style-type: none"> US3, US4, US10B, US26, US26D and BLK Anti-Microbial coating (US26D finish only)
Functions	Privacy (F76A)
Latchbolt Type	<ul style="list-style-type: none"> 1/2" (13 mm) throw, stainless steel 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate for 2-3/4" (70 mm) backset 1" x 2-1/4" (25 mm x 57 mm) faceplate for 2-3/8" (60 mm) backset
Lever Options	Archer, August and Withnell
Lock Chassis	Heavy gauge steel, zinc dichromated for corrosion resistance. Thru-posts are removable. Failure to install thru-posts and screws voids BHMA certification, UL rating, and warranty
Notes	<ul style="list-style-type: none"> No exposed mounting screws Non-handed
Options	<ul style="list-style-type: none"> Lead Lining Tactile Warning Split Finish
Rose Diameter	3-11/32" (85 mm)
Strikes	<ul style="list-style-type: none"> 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike Optional strikes available

Warranty

Lifetime