



PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

5100 CLOSER X HOLD OPEN ARM -  
HO

5100 HO



SPECIFICATIONS

Applications	<ul style="list-style-type: none"><li>Grade 1 Heavy Duty Surface Door Closer adjustable sizes 1–6</li><li>Ideal for schools, hospitals, and other high-use environments</li></ul>
Arm	5107 - Hold Open Arm
Box Quantity	1
Case Quantity	4
Certifications	<ul style="list-style-type: none"><li>BHMA Certified ANSI A156.4, adjustable sizes 1–6</li><li>ADA compliant ANSI A117.1 Accessibility Code</li><li>UL/cUL Listed for up to 3 hours</li><li>UL10C Positive Pressure Rated</li><li>UL10B Neutral Pressure Rated</li><li>5100 Door Closer EPD</li></ul>
Cover	<ul style="list-style-type: none"><li>Full plastic cover - standard</li><li>Plated metal cover - optional</li></ul>
Door Thickness	<ul style="list-style-type: none"><li>1–3/4" (44 mm) - standard</li><li>1–3/8" - 2–1/4" (36 mm - 57 mm) thick door - optional</li></ul>
Fasteners	<ul style="list-style-type: none"><li>Self-reaming, self-tapping wood and machine screws</li><li>Sex nuts and bolts</li></ul>
Finishes	ALM, BLK, BRZ, DBZ, GOL
Handing	Non-handed
Material	Forged steel arm
Maximum Door Weight	330 lbs.
Product Description	5100 Closer x 5107 Hold Open Arm (HO)
Springs	<ul style="list-style-type: none"><li>One piece seamless steel spring tube</li><li>Double heat-treated, steel-tempered springs</li><li>Precision-machined, heat-treated steel piston</li></ul>
Valves	<ul style="list-style-type: none"><li>Adjustable latching and sweep speed valves</li><li>Adjustable backcheck valve - standard</li><li>Delayed action valve - optional</li><li>Staked valves - standard</li></ul>

**Warranty**

Lifetime warranty