1000 SERIES HEAVY DUTY RIM EXIT DEVICE



Specification

ANSI: Meets ANSI - A156.3 - Grade 1 Standards

UL Listings: UL Listed for Panic Exit Hardware

(Optional) Fire Rating: UL Listed for "A" Label 3 Hour Fire Doors (no dogging on rated devices)

ADA: Meets ADA requirements ANSI A117.1 with Lever Trim

Handing: Non Handed • Completely Reversible

Construction: Heavy Duty Extruded Anodized Aluminum Channel & Steel Chassis

Finishes: US3, US4, US10B, US26 & US32D on Headcover, Pushbar & End Cap

Marine Grade: Marine Grade 316 Stainless Steel option available

Latchbolt: Deadlocking latchbolt with 5/8" projection

Strike: Roller Stike with 5/8" projection & 1/8" shim

Dogging: 5/32" Hex Key Dogging Standard on Panic Exit Hardware only

Cylinder Dogging: Cylinder Dogging Kits available for new or existing exit devices

Device Lengths: 33" for 3'-0" wide doors and 42" for 3-8" to 4'-0" wide doors

Min. Door Width: 33" device can be cut down to fit on 2'-8" wide door 42" device can be cut down to fit on 3'-4" wide door

Center Case Dim.: 8" Height x 2 7/8" Wide x 2 13/16" Thick - 4 1/2" Minimum stile required

Mechanism Case Dim.: 2 3/16" Height x 2 3/16" Wide

Projection: 3 3/8" Undogged • Pushbar Neutral & 2 13/16" Dogged • Pushbar Depressed

Fasteners: Wood, Machine & Self Tapping Machine Screws (F1000R includes thru bolts)

Trim & Accessories: ASA & latch fillers included, Exterior Trims, Shim Kits & other accessories available

Alarmed Exits: Exit Alarm Kit ALK-1000 available for new or existing devices

Electrification: ELR · Motorized Electric latch retraction, ED · Electric dogging, REX · Request to exit,

LBM - Latch bolt monitoring available, See electrified section

Warranty: Limited Lifetime Warranty





